

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Per metre Prices			Description
		≥100m	≥500m	TRADE	
Installation Cables - Audio					
AUDIO - MICROPHONE Event™ 220Series: LSZH FireFighter® <i>Pre-Jacketed starquad audio multicore with individually foil-shielded quads and overall foil shield.</i> Conductors: Oxygen free tinned copper, 7 x 0.20mm (0.22mm²)	ML4/1	1.35	1.14	0.87	1 x Quad install mic cable, with standard LSZH Jacket. 4.7mmØ - Grey Jacket
	220-6601	1.35	1.14	0.87	1 x Quad install mic cable, with PUR ultra-flexible Jacket 3.7mmØ - Black Jacket
	220-6604	8.23	6.93	5.27	4 x Quad install mic cable, with PUR ultra-flexible Jacket 11.1mmØ - Black Jacket
	220-6608	15.83	13.33	10.13	8 x Quad install mic cable, with PUR ultra-flexible Jacket 14.4mmØ - Black Jacket
AUDIO - TIE-LINES EventSeries® LSZH FireFighter®-jacketed <i>Audio Tie-line cables for both analogue and true 110Ω AES/EBU performance. Can also be used for DMX lighting control.</i> <i>Oxygen free tinned copper, 7 x 0.20mm (0.22mm²) cores, oxygen-free stranded tinned copper drain-wire (26AWG) with Aluminium/polyester tape screen (Alu. inside).</i> <i>Bend radius = 7.5 x Ø</i> <i>Working Temperature: -30° C to +85° C</i>	110-4501-01	0.56	0.47	0.36	1 x pair: Red/Black cores. 3.5mmØ - Black Jacket
	110-4601-**	0.56	0.47	0.36	1 x pair: Blue/White cores. 3.5mmØ - in choice of jacket-colours, as follows: ** add suffix: 02 (Black Jacket), 03 (Green), 04 (Red), 05 (Grey), 06 (Yellow), 08 (Orange), 10 (White), or 12 (Brown)
	110-i4602	1.87	1.58	1.20	2 x pair: Blue/White cores. 9.1mmØ - Black Jacket
	110-i4604	3.54	2.98	2.27	4 x pair: Blue/White cores. 10.7mmØ - Black Jacket
	110-i4608	4.89	4.12	3.13	8 x pair: Blue/White cores. 14.0mmØ - Black Jacket
	110-i4612	8.12	6.84	5.20	12 x pair: Blue/White cores. 17.1mmØ - Black Jacket
	110-i4616	12.50	10.52	8.00	16 x pair: Blue/White cores. 19.1mmØ - Black Jacket
	110-i4624	17.50	14.74	11.20	24 x pair: Blue/White cores. 25.6mmØ - Black Jacket
TPM (Thermoplastic Rubber) jacketed single-pair version	110-1601-01	0.54	0.45	0.35	1 x pair: Blue/White cores. 4.2mmØ - Black TPM Jacket (for fixed wiring of digital equipment and patch boards)
AUDIO - LOUDSPEAKER EventSeries® <i>LSZH FireFighter® Twin-Axial Loudspeaker cables with excellent flexibility</i> <i>Stranded oxygen-free bare copper.</i> <i>Bend radius = 10 x Ø</i> <i>Working Temperature: -5° C to +80° C (installed) / -20° C to +80° C (static)</i> <i>IEC 60332-1</i>	ZHP2075	0.73	0.61	0.47	2 x 0.75mm ² cores. 5.2mmØ - Black Jacket
	ZHP215	0.94	0.79	0.60	2 x 1.5mm ² cores. 6.0mmØ - Black Jacket <i>White-jacketed version available at same price - use code ZHP215-10</i>
	ZHP415	2.50	2.11	1.60	4 x 1.5mm ² cores. 7.3mmØ - Black Jacket
	ZHP225	1.67	1.40	1.07	2 x 2.5mm ² cores. 7.6mmØ - Black Jacket <i>White-jacketed version available at same price - use code ZHP225-10</i>
	ZHP425	3.13	2.63	2.00	4 x 2.5mm ² cores. 9.0mmØ - Black Jacket
	ZHP825	7.50	6.32	4.80	8 x 2.5mm ² cores. 12.1mmØ - Black Jacket
	ZHP240	2.71	2.28	1.73	2 x 4.0mm ² cores. 8.8mmØ - Black Jacket
	ZHP440	3.65	3.07	2.33	4 x 4.0mm ² cores. 10.2mmØ - Black Jacket
	ZHP840	10.00	8.42	6.40	8 x 4.0mm ² cores 13.6mmØ - Black Jacket
	ZHP260	3.65	3.07	2.33	2 x 6.0mm ² cores 10.4mmØ - Black Jacket

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Per metre Prices			Description
		≥100m	≥500m	TRADE	
AUDIO - LOUDSPEAKER (HOME CINEMA) Event™ 500-Series LSZH FireFighter® cables: <i>specifically designed for in-wall multi-room and home cinema installations.</i> Flame Retardancy: IEC 60332-1 (single cables) / IEC 60332-3 (bunched cables) Halogen Free: IEC 60754 series Smoke Emission: IEC 61034 series	5002C1444-01	1.46	1.23	0.93	2 x 14AWG / 1.6mm ² 7.2mmØ - Black Jacket
	5002C1644-07	0.83	0.70	0.53	2 x 16AWG / 1.3mm ² 6.0mmØ - Pink Jacket
	5004C1444-07	2.71	2.28	1.73	4 x 14AWG / 1.6mm ² 7.2mmØ - Pink Jacket
	5004C1644-07	1.46	1.23	0.93	4 x 16AWG / 1.3mm ² 7.15mmØ - Pink Jacket
Installation Cables - Broadcast					
VIDEO - Co-Axial EventSeries® LSZH FireFighter® Serial Video <i>A range of 75Ω HD Coaxial cables for installation and outside broadcast, up to and including versions for 4K/UHDTV(12G-SDI)</i>	HD300-01	0.63	0.53	0.40	1 x 0.3mm ² solid-core with screen and tinned copper braid cable. 2.54mmØ - Black Jacket HDTV and Serial Digital Video
	HD600-13	0.83	0.70	0.53	1 x 0.65mm ² solid-core with screen and tinned copper braid cable. 4.5mmØ - Turquoise Jacket Serial Digital Video Cable
	HD720-13	1.46	1.23	0.93	1 x 0.8mm ² solid-core with screen and tinned copper braid cable. 6.0mmØ - Turquoise Jacket Serial Digital video cable.
	HD1000	1.56	1.32	1.00	1 x 1.0mm ² solid-core with screen and tinned copper braid cable. 4.5mmØ - Turquoise Jacket Serial Digital Video Cable
	HD1630	3.54	2.98	2.27	1 x 1.63mm ² solid-core with screen and tinned copper braid cable. 10.2mmØ - Turquoise Jacket HD1630 HDTV and Serial Digital Video Cable 75Ω. Extremely Low-Loss for 4K / UHDTV (12G-SDI)
RF LSZH FireFighter® Coaxial cables for low-power signal and RF use.	RG58C/U-MIL LSZH	0.73	0.61	0.47	1 x 0.9mm ² co-axial, stranded (19/0,18 mm) RG58 50Ω. 6.0mmØ - Black jacket UV-resistant cable for low-power signal & RF use. 50mm bend-radius.
	RG59B/ULSZH-MIL	0.73	0.61	0.47	1 x 0.59mm ² co-axial, solid-core RG59 50Ω. 6.15mmØ - Black jacket UV-resistant cable for low-power signal & RF use. 50mm bend-radius.
	RG213/ULSZH	3.13	2.63	2.00	1 x co-axial, stranded (7 x 0,75mm). 10.3mmØ - Black Jacket UV-resistant cable for low-power signal & RF use. 5 x Ø bend-radius.
DIGITAL AUDIO AES/EBU Co-Ax cables for HD/SD applications	HD850-01	2.09	1.76	1.33	1 x 22AWG stranded-core with screen and tinned copper braid cable. 6.15mmØ - Black Jacket Serial Digital Video Cable
	HD920-01	3.02	2.54	1.93	1 x 1.1mm ² stranded-core with screen and tinned copper braid cable. 7.0mmØ - Black Jacket <i>Extended-distance</i> Serial Digital Video Cable for O/B vehicles etc
Hybrid Camera cables EventSeries® Camera Cables. <i>PVC Triax and LSZH FireFighter® SMPTE 311M Hybrid HDTV Fibre-Optic (for transmitting audio, power and HD-SDI video over longer distances).</i>	TRIAx14	6.05	5.09	3.87	1 x (7x 0.75mmØ) Triaxial Broadcasting Cable. 14.5mmØ - Red PVC Jacket <i>For simultaneous transmission of power and multiplex image signals between a camera and its control unit</i>
	406311M	6.66	5.61	4.27	Fibre-Optic Hybrid. Aux: 4 x 0.6mm stranded / Signal: 2 x 0.22mm ² stranded / Fibre Optic: 2 x 9/125µm Central element: 2.40mmØ (19 x 0.35mm Steel stranded) - Black outer jacket Bend radius (Dynamic / Static): 15 x Ø / 10 x Ø
	806311M	7.29	6.14	4.67	Fibre-Optic Hybrid. PUR jacketed cable for extra flexibility. Aux: 4 x 0.6mm ² stranded / Signal: 2 x 0.22mm ² stranded / Fibre Optic: 2 x 9/125µm. Central element: 2.15mmØ (19 x 0.30mm Steel stranded) - Black outer jacket Bend radius (Dynamic / Static): 15 x Ø / 10 x Ø

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Per metre Prices			Description
		≥100m	≥500m	TRADE	
Installation Cables - Digital Lighting Control					
HYBRID EventSeries® LSZH FireFighter® <i>Hybrid Control & Multimedia cables</i>	5000182434	1.25	1.05	0.80	For Lutron *GRAFIK EYE™ & Crestron touch-panels. (2 x 0.35mm) + (2 x 0.93mm). 7.5mmØ - Blue Jacket
	5000162224	1.52	1.28	0.97	For Blind Control. (2 x 0.35mm) + (2 x 1.32mm). 7.05mmØ - White Jacket
	500012221834	3.85	3.25	2.47	For Lutron *GRAFIK EYE™ over extended distance (max 600m, without repeater) (2 x 0.35mm) + (2 x 3.93mm) + (1 x 0.93mm) 7.2mmØ - Turquoise Jacket
	50005031	1.77	1.49	1.13	Scroller power & control. 1 x (2x16AWG) & 1 x (2x24AWG) 600V. 6.8mmØ - Black Jacket
DMX	DMXZH-01	1.14	0.96	0.73	1 x pair & screen LSZH FireFighter®110Ω. 5.75mmØ - Black jacket 60mm bend-radius
Installation Cables - CAT					
DATA - CAT - 305m boxes Draka <i>CAT6 & CAT6a LSHF cable, supplied in boxes of 305m</i>	60011113	n/a	(per box) 236.83	(per box) 180.00	CAT6a U/FTP 4 x pair 23AWG/0.258mm2 solid bare copper wires. 7.1mmØ - Pastel Blue (RAL 5024) Jacket Bend radius: 8 x Ø (dynamic) / 4 x Ø (static)
	60025433	n/a	(per box) 145.61	(per box) 110.67	CAT6 HD U/UTP 4 x pair 23AWG/0.258mm2 solid bare copper wires. 7.1mmØ - Violet (RAL4001) Jacket Bend radius: 15 x Ø (static) / 20 x Ø (dynamic)
DATA - CAT SureLAN® <i>CAT6 and CAT6a data cables in LSZH FireFighter®jackets</i>	5001	0.63	0.53	0.40	CAT6 U/UTP 4 x pair 20AWG/0.54mm2 solid bare copper wires. 6.15mmØ - Ivory Jacket Bend radius: 8 x Ø (dynamic) / 4 x Ø (static)
	5007	0.77	0.65	0.49	CAT6 F/UTP 4 x pair 24AWG/0.205mm2 solid bare copper wires. 7.0mmØ - Ivory Jacket Bend radius: 8 x Ø (dynamic) / 4 x Ø (static)
	7291	0.83	0.70	0.53	CAT6a F/UTP 4 x pair 23AWG/0.258mm2 solid bare copper wires. 7.1mmØ - Ivory Jacket Bend radius: 8 x Ø (dynamic) / 4 x Ø (static)
Industrial Ethernet: CAT 7 in industrial-grade PUR FHF jacket	6485	6.66	5.61	4.27	CAT7 SU/FTP 4 x shielded-pair (23 x 7AWG) stranded bare copper wires. 8.0mmØ - Black jacket Bend radius: 8 x Ø (tensile load) / 4 x Ø (without tensile load)
Installation Cables - SureLIGHT® FIBRE					
DATA - FIBRE SureLIGHT® <i>Tight-Buffered Distribution LSZH FireFighter® Fibre cables colour coded optical fibres</i>	104044TB-01	1.77	1.49	1.13	OM4, Cat A, 4-core 50/125 TBIDC. 6.0mmØ - Black Jacket Bend radius: 8 x Ø (dynamic) / 20 x Ø (static)
	104084TB-01	3.10	2.61	1.99	OM4, Cat A, 8-core 50/125 TBIDC. 7.3mmØ - Black Jacket Bend radius: 8 x Ø (dynamic) / 20 x Ø (static)
	104124TB-01	3.96	3.33	2.53	OM4, Cat A, 12-core 50/125 TBIDC. 8.3mmØ - Black Jacket Bend radius: 8 x Ø (dynamic) / 20 x Ø (static)
	108044TB-01	0.65	0.54	0.41	SMF, 4-core 9/25 TBIDC. 6.24mmØ - Black Jacket Bend radius: 15 x Ø (long-term) / 25 x Ø (short-term)
	108084TB-01	0.83	0.70	0.53	OS2, 8-core 9/125 TBIDC. 6.5mmØ - Black Jacket Bend radius: 15 x Ø (long-term) / 25 x Ø (short-term)
	108124TB-01	1.02	0.86	0.65	G652.D, 12-core 9/125 TBIDC. 7.3mmØ - Black Jacket Bend radius: 15 x Ø (long-term) / 25 x Ø (short-term)

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Per metre Prices			Description
		≥100m	≥500m	TRADE	
Installation Cables - Power					
EventSeries® LSZH FireFighter® ZHL multicore cables <i>Power cables for installation. Extra-supple compounds for good flexibility and mechanical resistance.</i> Bend Radius (all cables): 4 x Ø (fixed) / 7.5 x Ø (flexing)	ZHL-315-JB	1.35	1.14	0.87	3-core x 1.5mm ² . 8.3mmØ - Black Jacket
	ZHL-325-JB	2.19	1.84	1.40	3-core x 2.5mm ² . 10.0mmØ - Black Jacket
	ZHL1815	7.50	6.32	4.80	Socapex. 18 x 1.5mm ² . 14.8mmØ - Black Jacket
	ZHL1825	9.38	7.89	6.00	Socapex. 18 x 2.5mm ² . 18.0mmØ - Black Jacket
FF90 LSZH FireFighter® Panel Wires <i>Bend radius (all wires):</i> 4 x Ø (fixed) / 6 x Ø (occasionally moved) Available in a choice of 8 x different jacket-colours , as shown on right	4002504-**	0.63	0.53	0.40	1 x 2.5mm ² . ** add suffix: 01 (Black Jacket), 02 (Blue), 03 (Green), 04 (Red), 05 (Grey), 06 (Yellow), 11 (Green/Yellow), or 12 (Brown)
	4004004-**	0.83	0.70	0.53	1 x 4.0mm ² . ** add suffix: 01 (Black Jacket), 02 (Blue), 03 (Green), 04 (Red), 05 (Grey), 06 (Yellow), 11 (Green/Yellow), or 12 (Brown)
	4006004-**	1.56	1.31	1.00	1 x 6.0mm ² . ** add suffix: 01 (Black Jacket), 02 (Blue), 03 (Green), 04 (Red), 05 (Grey), 06 (Yellow), 11 (Green/Yellow), or 12 (Brown)
Touring Cables - Audio Signal					
AUDIO - MICROPHONE / INSTRUMENT					
EventSeries® Microphone Cables <i>For flying leads. Kevlar reinforced strain relief</i>	MLX2-**	1.04	0.88	0.67	1 x pair & screen mic cable for flying leads. MLX2 oxygen-free with LAP screen, enlarged sheath & Kevlar strain-relief. 6.35mmØ - in choice of jacket-colours, as follows: ** add suffix: 01 (Black), 02 (Blue), 03 (Green), 04 (Red), 05 (Grey), 06 (Yellow), 07 (Orange), or 8 (Violet)
	MLX4	1.25	1.05	0.80	1 x Quad Starquad mic cable . MLX2 with LAP screen, enlarged sheath & Kevlar strain-relief. 7mmØ - Black Jacket
EventSeries® Instrument/Guitar Cable <i>For flying leads.</i>	ICEX1-01	1.14	0.96	0.73	Unbalanced double-shielded Instrument Cable with enlarged outer-sheath. 6.2mmØ - Black Jacket
AUDIO - TIE-LINES					
EventSeries® <i>Multi Pair Analogue/Digital Audio Cables for use as flying leads in touring applications. Pre-Jacketed digital/analogue audio multi cores with individually foil-shielded pairs and overall foil shield. Very flexible and tough TPM sheath. Impedance of 110Ω AES/EBU is perfect for both analogue and AES/EBU signals - as well as DMX lighting-control.</i>	110-1602	2.06	1.74	1.32	2 x pair: 9.2mmØ - Black Jacket
	110-1604	3.13	2.63	2.00	4 x pair: 10.8mmØ - Black Jacket
	110-1608	5.21	4.39	3.33	8 x pair: 14.5mmØ - Black Jacket
	110-1612	7.50	6.32	4.80	12 x pair: 17.5mmØ - Black Jacket
	110-1616	10.42	8.77	6.67	16 x pair: 19.2mmØ - Black Jacket
	110-1624	16.25	13.68	10.40	24 x pair: 24mmØ - Black Jacket

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Per metre Prices			Description
		≥100m	≥500m	TRADE	
Touring Cables - Loudspeaker					
EventSeries® <i>Tour Grade VHP Loudspeaker Cable for flying leads. Extra-supple compounds for soft & pliable flexibility and strength.</i>	VHP215	1.25	1.05	0.80	2 x 1.5mm ² cores, twin-axial Touring spkr cable. 6.25mmØ - Black Jacket
	VHP225	1.77	1.49	1.13	2 x 2.5mm ² cores, twin-axial Touring spkr cable. 7.40mmØ - Black Jacket
	VHP425	3.13	2.63	2.00	4 x 2.5mm ² cores Touring spkr cable. 10.25mmØ - Black Jacket
	VHP825	8.23	6.93	5.27	8 x 2.5mm ² cores Touring spkr cable. 15.80mmØ - Black Jacket
	VHP440	4.79	4.03	3.07	4 x 4.0mm ² cores Touring spkr cable. 12.20mmØ - Black Jacket
	VHP840	12.29	10.35	7.87	8 x 4.0mm ² cores Touring spkr cable. tbc mmØ - Black Jacket
Touring Cables - DATA					
DATA - CAT <i>Tactical Ethernet cables for flying leads</i>	2442	1.98	1.66	1.26	CAT5e U/UTP 24/7AWG 4 x pair (stranded) with flexible polymer compound Dual-Jacket 7.50mmØ - Black Jacket Outer jacket can be removed to facilitate termination to RJ45
	6485	6.66	5.61	4.27	CAT7 SU/FTP 23/7awg 4 x pair (stranded). Flexible PUR FHF Jacket & wire braid. 8.0mmØ - Black Jacket
DATA - DMX <i>110Ω DMX cable for flying leads. Outer-jackets in choice of FRLS (Flame-Retardant Low-Smoke) or TPE (Thermoplastic Elastomer). Individually-jacketed Black & Red 16 x 0.20mm (0.5mm²) cores.</i>	DMX-01	1.04	0.88	0.67	1 x pair & screen, 500V FRLS . 5.75mmØ - Black Jacket
	DMX-04	1.04	0.88	0.67	1 x pair & screen, 500V FRLS . 5.75mmØ - Red Jacket
	DMX-P-01	1.25	1.05	0.80	1 x pair & screen, 600V TPE . 5.75mmØ - Black Jacket
Touring Cables - POWER					
SUPremeFlex Harmonised Rubber Cable <i>Flame- and oil-retardant & self-extinguishing for flying power leads. EM2 Elastomer outer sheath. For use in ambient temperatures down to -25^o C and up to 50^o C on-cable-surface temperature.</i>	H07RN-F31.5	1.56	1.32	1.00	3 x 1.5mm ² H07RN-F. c10.0mmØ - Black Jacket
	H07RN-F32.5	2.06	1.74	1.32	3 x 2.5mm ² H07RN-F. c13.0mmmmØ - Black Jacket
	H07RN-F41.5	2.29	1.93	1.47	4 x 1.5mm ² H07RN-F. c12.0mmØ - Black Jacket
	H07RN-F42.5	2.92	2.46	1.87	4 x 2.5mm ² H07RN-F. c14.0mmØ - Black Jacket
	H07RN-F56	7.50	6.32	4.80	5 x 6.0mm ² H07RN-F. c20.0mmØ - Black Jacket
Socapex FHL <i>Soft Thermoplastic Polymer-jacketed 18-core cables for Socapex flying leads. Bend radius (all wires): 4 x Ø (fixed) / 7.5 x Ø (flexing)</i>	FHL1815	7.08	5.96	4.53	18 x 1.5mm ² H07RN-F. 14.8mmØ - Black Jacket
	FHL1825	8.75	7.37	5.60	18 x 2.5mm ² H07RN-F. 18.1mmØ - Black Jacket



Audio Visual, Broadcast and Entertainment Technology Bulk Cable & Accessories

2B Heard Ltd
 Unit 4F, Shefford Industrial Estate
 St Francis Way
 Shefford
 Bedfordshire SG17 5DZ
 Tel: +44 (0) 330 088 9271
 W: www.2b-heard.com

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). Prices subject to change without notice.

Range	Stock Code	Unit Prices			Description
		Unit	List	TRADE	
CONNECTORS					
BNC Connectors	BNC1C59	each	0.98	0.69	BNC: for RG59B-U / RG62A-U / RG210 / URM70, Male (Jack), Crimp - use Tool kit ref TL-9565
75Ω BNC connectors Nickel bodies and brass pins. See below for our range of compatible Termination Tools	BNC1C1/3	each	1.19	0.84	BNC: for PSF1-3, Male (Jack), Crimp - use Tool kit ref TL-9565
	BNC1C179	each	1.85	1.31	BNC: for G179 / 658500 / RG187A-U / URM111, Male (Jack), Crimp - use Tool kit ref TL-9565
	BNC1C11	each	5.86	4.13	BNC: for RG11, Male (Jack), Crimp - use Tool kit ref TL-9565
	BNC High Definition Connectors	BNC1CHD300-12G	each	2.08	1.47
Event HD-BNC 12GHz HD Connectors High-performance professional connectors to properly complement the performance of our HD cable range. Featuring nickel or chrome-plated turned-brass bodies with gold-plated contacts. Cable-compatibility is indicated in each connector's Description. TERMINATION: The ideal tool to effect the best termination is also indicated in the connector's Description. See below for our range of compatible Termination Tools	BNC1CHD300-12G-01	each	2.08	1.47	BNC: for HD300, Male (Jack), Crimp (Black) - use Tool ref TL-1007HD
	BNC1CHD600-12G-01	each	2.27	1.60	BNC: for HD600, Male (Jack), Crimp (Black) - use Tool ref TL-1007HD
	BNC1CHD600-12G	each	2.27	1.60	BNC: for HD600, Male (Jack), Crimp (Nickel) - use Tool ref TL-1007HD
	BNC1CHD720-12G-01	each	2.48	1.75	BNC: for HD720, Male (Jack), Crimp (Black) - use Tool ref TL-1021HD
	BNC1CHD720-12G	each	2.48	1.75	BNC: for HD720, Male (Jack), Crimp (Nickel) - use Tool ref TL-1021HD
	BNC1CHD920-12G-01	each	3.02	2.13	BNC: for HD920, Male (Jack), Crimp (Black) - use Tool ref TL-1027HD
	BNC1CHD920-12G	each	3.02	2.13	BNC: for HD920, Male (Jack), Crimp (Nickel) - use Tool ref TL-1027HD
	BNC1CHD1000-12G-01	each	2.17	1.53	BNC: for HD1000, Male (Jack), Crimp (Black) - use Tool ref TL-1021HD
	BNC1CHD1000-12G	each	2.17	1.53	BNC: for HD1000, Male (Jack), Crimp (Nickel) - use Tool ref TL-1021HD
	BNC1CHD1630-12G-01	each	5.48	3.87	BNC: for HD1630, Male (Jack), Crimp (Black) - use Tool ref TL-1002HD
	BNC1CHD1630-12G	each	5.48	3.87	BNC: for HD1630, Male (Jack), Crimp (Nickel) - use Tool ref TL-1002HD
	RJ45 Connectors	PXCAT6	Pack of 50	23.63	16.67
PXCAT6S8XL		Pack of 50	51.98	36.67	RJ45 Shielded: CAT5e / 6 / 6a. For stranded or solid wire from 22-26AWG with cores up to 1.15mm Ø Polycarbonate housing, Nickel-plated copper Shielding & gold-plated contacts
PXCAT6S4		Pack of 50	56.70	40.00	RJ45 Shielded: Round CAT5e, 6, 6A FTP. Up to 8mm Ø with stranded or solid cores up to 1.5mm Ø Polycarbonate housing, Nickel-plated copper Shielding & gold-plated phosphor-bronze contacts
PGSXL		Pack of 10	26.46	18.67	RJ45 Shielded: CAT6 / 6a. For XXL cables up to 8mm Ø with stranded or solid cores up to 1.5mm Ø Polycarbonate housing, brass shell & gold-plated phosphor-bronze contacts



Audio Visual, Broadcast and Entertainment Technology Bulk Cable & Accessories

2B Heard Ltd
 Unit 4F, Shefford Industrial Estate
 St Francis Way
 Shefford
 Bedfordshire SG17 5DZ
 Tel: +44 (0) 330 088 9271
 W: www.2b-heard.com

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Unit Prices			Description
		Unit	List	TRADE	
Socapex-compatible 6-Circuit Connectors Showline Connectors <i>High-performance Touring-grade 6-circuit lighting-power connectors, compatible with Socapex. Very rugged machine-aluminium construction for heavy-duty interior and exterior touring use.</i> * Rated 600VAC. Each of the 6 x circuits rated 23A continuous load. * IP67 when mated (note - IP67 rating achieved <u>only</u> when mated with another Showline connector) * 12 interlocking keys - help prevent the interior spinning within housing * Silver-plated brass contacts for high conductivity * Tempered-Spring female contacts to maintain constant low-resistance connection with mated plugs. * All-Black, hard-wearing finish to blend-in with stage environment CABLES: Use our ref FHL1815 or FHL1825 for making-up Touring leads and ref ZHL1815 or ZHL1825 for installation. see the Touring Cables - POWER section	SHLB19-LF-C-M40-S-014-S	each	45.79	32.31	Inline 19-pin Female (crimp terminations): cable O/D 15-23mm
	SHLB19-LF-S-M40-S-014-S	each	45.79	32.31	Inline 19-pin Female (solder terminations): cable O/D 15-23mm
	SHLB19-LM-C-M40-S-014-S	each	44.26	31.23	Inline 19-pin Male (crimp terminations): cable O/D 15-23mm
	SHLB19-LM-S-M40-S-014-S	each	44.26	31.23	Inline 19-pin Male (solder terminations): cable O/D 15-23mm
	SHLB19-LF-C-M40-S-014-0/S	each	45.79	32.31	Inline 19-pin Female (crimp terminations): cable O/D 26-32mm
	SHLB19-LF-S-M40-S-014-0/S	each	45.79	32.31	Inline 19-pin Female (solder terminations): cable O/D 26-32mm
	SHLB19-LM-C-M40-S-014-0/S	each	44.26	31.23	Inline 19-pin Male (crimp terminations): cable O/D 26-32mm
	SHLB19-LM-S-M40-S-014-0/S	each	44.26	31.23	Inline 19-pin Male (solder terminations): cable O/D 26-32mm
	SHLB19-PM-C-S	each	24.97	17.61	Panel-mount 19-pin Male Crimp
	SHLB19-PM-S-S	each	24.97	17.61	Panel-mount 19-pin Male Solder
	SHLB19-PF-C-S	each	26.65	18.80	Panel-mount 19-pin Female Crimp
	SHLB19-PF-S-S	each	26.65	18.80	Panel-mount 19-pin Female Solder
Socapex-compatible "Spider" Connectors Showline Connectors <i>Manufactured to the same specification as the Showline connectors above, these are specifically designed to accommodate six individual 3-core mains flexes to facilitate the manufacture of 6 x circuit break-out "spiders" - either a Male 19-pin to 6 x individual 15A or 16A 3-pin in-line sockets, or a Female 19-pin to 6 x individual 15A or 16A 3-pin in-line plugs.</i> CABLES: Ideal cables for making-up spiders are our ref H07RN-F31.5 or ref H07RN-F32.5 - see the Touring Cables - POWER section above.	SHLB19-LM-C-SPR10-S	each	72.58	51.20	Spider 19-pin Male (crimp terminations) for 3-core 1.5mm cable
	SHLB19-LF-C-SPR10-S	each	77.68	54.80	Spider 19-pin Female (crimp terminations) for 3-core 1.5mm cable
	SHLB19-LM-S-SPR10-S	each	72.58	51.20	Spider 19-pin Male (solder terminations) for 3-core 1.5mm cable
	SHLB19-LF-S-SPR10-S	each	77.68	54.80	Spider 19-pin Female (solder terminations) for 3-core 1.5mm cable
	SHLB19-LM-C-SPR12-S	each	72.58	51.20	Spider 19-pin Male (crimp terminations) for 3-core 2.5mm cable
	SHLB19-LF-C-SPR12-S	each	77.68	54.80	Spider 19-pin Female (crimp terminations) for 3-core 2.5mm cable
	SHLB19-LM-S-SPR12-S	each	72.58	51.20	Spider 19-pin Male (solder terminations) for 3-core 2.5mm cable
	SHLB19-LF-S-SPR12-S	each	77.68	54.80	Spider 19-pin Female (solder terminations) for 3-core 2.5mm cable



Audio Visual, Broadcast and Entertainment Technology Bulk Cable & Accessories

2B Heard Ltd
 Unit 4F, Shefford Industrial Estate
 St Francis Way
 Shefford
 Bedfordshire SG17 5DZ
 Tel: +44 (0) 330 088 9271
 W: www.2b-heard.com

Sept 2020 UK TRADE PRICE LIST in Sterling (Unit prices, VAT excluded). *Prices subject to change without notice.*

Range	Stock Code	Unit Prices			Description
		Unit	List	TRADE	
TOOLS					
BNC Crimping Tools <i>High-quality precision-made termination tools that match our cables and connectors.</i>	TL-2079	each	69.93	49.33	Tool: Cable-Cutter/Stripper/Crimper: for round cables CAT5e to 7, UTP & FTP <i>Crimps standard RJ45 and Oversized RJ45 plugs with only 1 compression point</i>
	TL-1002HD	each	94.50	66.67	Tool: BNC Crimper c/w 2.54 mm, 3.25 mm & 10.90 dies for: <i>HD1630 12GHz, RG8, RG11, RG174, RG179 & RG213 connectors</i>
	TL-1007HD	each	94.50	66.67	Tool: BNC Crimper: HD300 / HD600 12GHz connectors <i>Hardened-steel ratchet-controlled crimp</i>
	TL-1021HD	each	94.50	66.67	Tool: BNC Crimper c/w 1.07mm, 4.52mm, 6.48mm & 7.06mm dies for: <i>HD300, HD720 & HD1000 connectors</i>
	TL-1027HD	each	143.64	101.33	Tool: BNC Crimper c/w 6.48mm, 5.41mm, 2.49mm, 1.73mm & 8.15mm dies for: <i>RG6, RG58, RG59 & RG62 connectors</i>
	TL9565	each	151.20	106.67	RG Tool Kit containing: Coax crimp frame, 6.5" cable-cutter (max 10.5mm Ø), 4" L Coax Stripper, 5 x dies & screwdriver <i>All you need for crimping a huge range of RG-type cables into a wide range of connectors. Supplied c/w carry-case</i>
DELIVERY CHARGES					
Direct from the main warehouse <i>Cable is often urgently required on-site.. We can get it to you quickly!</i> PLEASE NOTE: <i>Next-day deliveries can only be effected within UK-mainland locations. Some more remote areas may also require longer than 24 working hours for carriers to deliver - please call for more information.</i>	DelCab-SDSV	each	-	82.80	SAME DAY (within M25): Small Van
	DelCab-SDLV	each	-	130.80	SAME DAY (within M25): Large Van
	DelCab-FSND	each	-	FOC	FOC STANDARD NEXT-DAY (delivery between 09:00-17:00). SPECIAL OFFER FOR ORDERS VALUED AT ≥£350
	DelCab-SND	each	-	15.00	STANDARD NEXT-DAY (delivery between 09:00-17:00)
	DelCab-ND09	each	-	54.00	NEXT-DAY EXPRESS (delivery before 09:00)
	DelCab-ND10	each	-	42.00	NEXT-DAY FAST (delivery before 10:00)
	DelCab-ND12	each	-	24.00	NEXT-DAY BEFORE NOON (delivery before 12:00)
	<i>Nett prices - no Trade-discount on deliveries</i>				