



## Description

The Lyzard-KZ14 I is an ultra-micro line array speaker in the smallest K-array's mid-high speaker series. With a small ultra-resistant milled aluminum enclosure measuring 2.2 x 10 cm x 1.2 cm and weighing only 59g, the Lyzard-KZ14 I delivers uncompromised audio performance with minimum residual noise. The compact size makes it the perfect solution for discreet audio integration in environments such as private accommodations, retail spaces, restaurants, bars, and museums.

The 4 x 1 high-efficiency transducers feature neodymium magnets and suspensions engineered for maximum linear excursion and minimum residual noise.

With a vertical coverage of 40° and horizontal of 140°, it is the smallest model with PAT array technology. With a frequency response of 500 Hz to 18 kHz, and an impressive peak SPL of 98 dB, the Lyzard-KZ14 I delivers clear audio reproduction and excellent intelligibility.

To complete the full frequency range, the Lyzard-KZ14 I has to be paired with one or more Truffle or Rumble subwoofers driven by a Kommander amplifier. The speaker can also be customized with any RAL color painting or premium finishes such as polished aluminum, 24K gold, rose gold or antique gold plating.

The front of the loudspeaker's small cabinet is protected by a removable magnetic grille for easy access during setup and maintenance. The rear panel includes a small two-pole screw Euroblock connector for easy connection.

The Lyzard-KZ14 I and KZ14R I are the perfect products for discreet audio integration in a variety of environments, leaving both your eyes fulfilled and your ears satisfied with their unique and sleek design.

The main product models and codes are:

KZ14 I black model

KZ14 I W white model

KZ14 I X customizable color (box + grille)

All Lyzard-KZ14 I components are designed by the K-array R&D department and are custom-made under the K-array quality control system in Italy.

Technical Specifications	
Type	Line Array PAT
Transducers	4 x 0.5" Neodymium magnet woofers
Frequency Response <sup>1</sup>	500 Hz - 18 kHz (-6 dB)
Max SPL <sup>2</sup>	98 dB (peak)
Coverage	V. 40°   H. 140°
Power Handling	15 W
Nominal Impedance	16 Ω
Connectors	IN+ IN- screw terminals

Handling & Finishes	
Material	Aluminum
Color	Black, White, Custom RAL
Finishes	24K Gold, Rose Gold, Antique Gold, Polished
IP Rating	IP64
Dimensions (WxHxD)	22 x 100 x 11 mm (0.9 x 3.9 x 0.4 in)
Weight	0.059 kg (0.130 lb)

<sup>1</sup> With dedicated preset.

<sup>2</sup> Maximum SPL is calculated using a signal with crest factor 4 (12dB) measured at 8 m then scaled at 1 m.

# Lyzard-KZ14I

